



518-111 Recycled Latex Interior Paint

Type	Acrylic
Gloss Level	Velvet / 7% - 15% (85°)
Viscosity	95 – 100 K.U
Coverage	40 m ² / 3.78L
Cleaning of Application Tools	Water
Size	3.78 liters
Drying Time	To Touch : 30 at 60 min. Reapply : 6 – 9 hours
Concentration of Solids	Per weight : 40% - 60%
VOCs	43 g/L (moyenne)

Colours

○	5181 - 10	MOONLIGHT WHITE*
●	5181 - 15	COTTON*
●	5183 - 22	EVERLASTING
●	5383 - 93	LINEN ¹
●	5183 - 24	CASTLE IN THE CLOUDS
●	5183 - 72	GREIGE
●	5183 - 05	WHITE CLAY
●	5183 - 70	PEARLY GREY*
●	5183 - 71	MODERNITY
●	5383 - 91	STONE GREY ¹
●	5183 - 38	THUNDER
●	5183 - 33	SUNSHINE
●	5183 - 28	MILLENNIUM PINK
●	5183 - 27	AZURE
●	5383 - 76	EVERGREEN
●	5383 - 81	GALAXY
●	5383 - 49	TRUFFLE ¹
●	5183 - 99	COAL

* Also available in 18.9 litres format

¹Pearl finish, increased washability. Interior and exterior.

Description

Premium, recycled, low-sheen velvet latex paint for use in most areas of the house such as walls and ceilings.

Colour**

This product should not be tinted to preserve its properties.

Colour may vary slightly from batch to batch.

**** Colours reproduced on paper may differ from actual paint colours.**

Storage

Keep in a dry, well ventilated area under moderate temperatures (20°C). Keep from freezing.

Restrictions

Do not apply in direct sunlight, high humidity and/or in excessive heat.

Do not use this paint in bathrooms, roofs, patios or flooring.

Do not apply this paint on bare metals. Primer is required.

WARNING : Keep out of the reach of children. Keep from freezing.

Consult with your municipality in order to dispose of used paint properly or use the following link: ecopeinture.ca/en/



5 8 -

Recycled Latex Interior Paint

Surface Preparation

Surface preparation is essential. Surfaces must be free of contaminants, mildew and peeling paint. Glossy surfaces should be sanded to ensure adherence of the product. Clean surfaces to be painted with TSP (Trisodium phosphate), rinse and allow to dry thoroughly.

Gypsum : apply a latex primer. (5188-05)

Bare Wood (resinous) : according to wood type (pine, spruce, cedar) apply one coat of primer, then proceed with 2 coats of this product.¹

Bare Wood (non-resinous) : Apply a first coat thinned to 15%. Then apply a second coat.

Alkyd Painted Surface : Apply a transition primer then 2 coats of this product.¹

Latex Painted Surface : Sand to remove the finish and reduce shine in glossy areas. Remove dust. Apply product.

Application

Thoroughly mix contents to ensure a consistent and homogeneous mixture. Use a synthetic paintbrush (nylon or polyester) or a 13 mm lint-free roller. When using a spraygun dilute to a 10% to 15% ratio for a uniform application.

Temperature must range between 10°C - 32°C. Humidity levels must be lower than 50%. The room must be well ventilated. For an ultimate finish, two coats should be applied. Allow to dry thoroughly before applying the second coat. Drying time may vary depending on temperature, humidity, aeration and paint thickness applied.

Cleaning of Application Tools

Clean with water and a mild soap.

Maintenance Instructions

It is best to use a soft cloth or sponge and a mild household soap. Do not use abrasive cleaners and/or greasy soaps. Rinse soap residue thoroughly. To enable full performance of this paint, allow at least 3 - 4 weeks prior to a first wash or when testing adhesion.

You can visit our website at boomerangpaint.com or write to us at info.boomerang@laurentide.co

¹ For additional information or inquiries, do not hesitate to contact our client services department specialist.





5383 - ■■■

Recycled Paint - Walls, Floors and Patios – Int. / Ext.

Type	Acrylic
Gloss level	Pearl / 20% - 25% (85°)
Viscosity	95-100 K.U
Coverage	40 m ² / 3.78L
Cleaner	Water
Size	3.78 liters
Drying Time	To touch : 30 to 60 min Reapply : 6 – 9 hours
Concentration of solids	Per weight : 40 - 60%
COVs	43 g/L (average)

Colours

- 5383 - 93 LINEN
- 5383 - 91 STONE GREY
- 5383 - 49 TRUFFLE

Description

A premium quality pearl gloss, recycled paint. Can be used indoors and outdoors on walls, floors and patios. A resin is added to render the product more resistant.

Colour**

This product should not be tinted to preserve its properties.

Colours may vary slightly from batch to batch.

****Colours reproduced on paper may differ from actual paint colours.**

WARNINGS : Keep out of the reach of children. Keep from freezing.

Storage

Keep in a dry well ventilated area under moderate temperatures (20°C).

Restrictions

Do not apply in direct sunlight, in high humidity and/or in excessive heat.

Do not use this paint for kitchens, bathrooms or on roofs.

Do not apply this paint on bare metals. Primer is required.

Surface Preparation

Surface preparation is essential. All surfaces must be free of contaminants, mildew or peeling paint.

Glossy areas have to be sanded to ensure proper adhesion. Then wash with TSP (Trisodium phosphate) rinse well, and allow to dry thoroughly.

Consult with your municipality in order to dispose of used paint properly or use the following link: ecopeinture.ca/en/



5383 - ■■

Recycled Paint - Walls, Floors and Patios – Int. / Ext.

Bare Wood (non-resinous) : Apply first coat thinned to 15%. Apply second coat as is.

Bare Wood (resinous) : according to wood type (pine, spruce, cedar) previously apply anti-bleeding primer. Then two coats of this product.

Alkyd Painted Surface : Do an adequate sanding. Removed all dust. Apply a transition primer and two coats of this product.¹

Latex Painted Surface : Thoroughly sand the finish to remove shine. Remove all dust. Apply as is.

Gypsum : Apply a first coat thinned to 15% or a latex primer, then 2 coats as is.

Concrete, Cement : Concrete must be dry before being painted, new concrete must cure at least one month per inch of thickness. Wash with muriatic acid and rinse thoroughly. Allow to dry. Apply first coat diluted with 10-15% of water.¹

Application

Shake well before using. Use a synthetic paintbrush (nylon or polyester) or a 10 mm lint-free roller. You must dilute with water to a 10 to 15% ratio when using a spraygun to produce a uniform application.

Temperature must be between 10°C - 32°C. Humidity level must be lower than 50% and the room must be well ventilated. For a premium finish, two coats should be applied. Allow an adequate drying time before reapplying.

Cleaning of Tools

Clean with water and a mild soap.

Maintenance Instructions

It is best to use a soft cloth or sponge and a mild household soap. Do not use abrasive cleaners and/or greasy soaps. Rinse soap residue. To enable full performance of this paint, allow 3 – 4 weeks prior to a first wash.

You can visit our website at boomerangpaint.com or write to us at info.boomerang@laurentide.co

¹For additional information or inquiries, do not hesitate to contact our customer service department specialist.

Prior to using this product, consult the Material Safety Data Sheet, for the use of Protective Equipment (section 8), for Preventive Measures (section 7), and First Aid and Emergency Procedures (section 4). The above mentioned data is provided by Laurentide Re\Sources Inc. for information purposes only. It does not constitute in any way as a promise or guarantee as for the use, duration or quality of this product since application conditions are beyond their control. This product must be used in strict accordance with the mentioned specifications alongwith any other instructions, warnings and guidelines issued by Laurentide Re\Sources Inc.
2019-09-27 V4.2





5188-05

Recycled Primer-Sealer and Undercoater – Interior

Type	Acrylic
Viscosity	95 – 100 K.U
Coverage	40 m ² / 3.78L
Cleaner/thinner	Water
Size	3.78 liters and 18.9 liters
Drying time	Touch : 30 to 60 minutes Recoat : 6 hours
Concentration of solids	Per weight : 40 to 60 %
COV	43 g/L (average)
Color	5188-05 WHITE

Description

Recycled interior acrylic primer-sealer and undercoater for new or acrylic painted surfaces. Can be used in any room of the house, for their walls and ceiling. Easy to apply, excellent adherence, non-splattering and excellent hiding capacities.

Colour

This product should not be tinted to preserve the maximum sealing and adherence capacities.

Colour may vary slightly from batch to batch.

WARNINGS: Keep from freezing.
Keep out of the reach of children.

Storage

Keep in a dry and well ventilated area in moderate temperatures (20°C). Keep from freezing.

Restriction

Do not apply in high humidity or during excessive heat or under an ardent sun.

This product is not recommended on resinous wood.

Do not use this primer on the floor.

Surface preparation

Surface preparation is crucial and the successful outcome of your project depends on it. All surfaces must be free from contaminants, mildew or peeled paint. Glossy areas have to be sand to ensure a better adhesion. Wash all surfaces to be painted with TSP (Trisodium phosphate) and rinse well. Allow proper time for drying.

Consult with your municipality in order to dispose of used paint properly or use the following link: ecopeinture.ca/en/

Prior to using this product, consult the Material Safety Data Sheet, for the use of Protective Equipment (section 8), Preventive Measures (section 7), and First Aid and Emergency Procedures (section 4). The above mentioned data is provided by Laurentide Re\Sources Inc. for information purposes only. It does not constitute in any way as a promise or guarantee as for the use, duration or quality of this product since application conditions are beyond their control. This product must be used in strict accordance with the mentioned specifications alongwith any other instructions, warnings and guidelines issued by Laurentide Re\Soures Inc.

2018-09-27 v 4.0

FT 5188-05



5188-05

Recycled Primer-Sealer and Undercoater – Interior

Gypsum : Plaster must be clean and dry before painting. Make sure all dust has been removed after sanding.

Bared wood (resinous) : According to wood type (pine, spruce, cedar...) apply anti-bleeding primer.

Bared wood (non-resinous) : Apply a first coat thinned 15%. Apply second coat as it is.

New concrete, cement : New concrete must be dry before being painted. It must dry at least one month per inch of thickness. Wash with muriatic acid and rinse thoroughly. Apply one coat as is.

Latex painted surfaces : Apply as is.

Alkyd painted surfaces : Sand well then clean for an optimized adherence, transition primer is recommended.

Application

Thoroughly shake the paint can and then use a stir stick to mix the content all the way to the bottom of the can. Use a synthetic paintbrush (nylon or polyester) or a 10 mm anti-lint roller. The primer must be diluted with water up to 10 % ratio in order to use a sprayer and get an even spread.

Temperature must be between 10°C and not over 32°C. The humidity level must be lower than 50% and the room must be well ventilated. Drying time may vary depending on temperature, air moisture and thickness of paint applied.

Cleaning of tools

Clean with water and soft soap.

Instruction for maintenance

It is best to use a soft cloth or sponge and a mild household soap. Do not use abrasive cleaner and/or fatty soap. Rinse soap scum. To allow a full capacity of this paint, wait at least 3 – 4 weeks prior to a first wash or to test adhesion.

You may also go on our website at boomerangpaint.com or write to us at info.boomerang@laurentide.co

¹ For complementary information and recommendation for those substrates, if necessary, do not hesitate to consult our customer service department specialist.

Prior to using this product, consult the Material Safety Data Sheet, for the use of Protective Equipment (section 8), Preventive Measures (section 7), and First Aid and Emergency Procedures (section 4). The above mentioned data is provided by Laurentide Re\Sources Inc. for information purposes only. It does not constitute in any way as a promise or guarantee as for the use, duration or quality of this product since application conditions are beyond their control. This product must be used in strict accordance with the mentioned specifications alongwith any other instructions, warnings and guidelines issued by Laurentide Re\Sources Inc.
2019-09-27 v 4.0

